



SUBLI 1510+
HIGH-EFFICIENCY DUAL-PLATE
SUBLIMATION HEAT PRESS



SUBLIMAXI 2513
EXTRA-LARGE FORMAT
INDUSTRIAL HEAT PRESS

Equip photo labs, photographers, and commercial print shops with professional-grade equipment for world-class production.

Applications

- Textiles
- Rigid Supports
- Sporting Goods
- Advertising
- Large Format

Feature	SUBLI 1510+	SUBLIMAXI 2513
Weight	1000 kg	2180 kg
Pressure	296 gr/cm ² (8 bars)	318 gr/cm ² (5.5 bars)
Max Temperature	220°C / 429°F	220°C / 429°F
Power Supply	400 V - 3 phases	400 V - 3 phases
Electric Power	20.25 kW	35 kW
Amperage	32 A	56 A
Working Area	1570 x 1070 mm	2550 x 1300 mm
Max Product Thickness	25 mm	25 mm
Heating Zones	2 zones	4 zones

Advanced Electronics

- **PID Control:** Precise and fast temperature regulation.
- **Adaptive Settings:** Parameters optimized for flex, textile, and rigid supports.
- **Memory:** 10 storable programs and a resettable counter.
- **Monitoring:** Double timer (0-60 min) and heat control up to 220°C.
- **Accuracy:** +/- 1% precision on all time and temperature settings.

Key Features

- **Perfect Heat Distribution:** Utilizes multi-zone heating for consistent results.
- **User-Friendly Interface:** Equipped with a new 7" touch screen for easy operation.
- **High Efficiency:** Features a fast start-up time of 20 minutes.
- **Optimized Workflow:** Double motorized sliding trays and front loading.
- **Advanced Control:** Improved regulation and new programming capabilities.
- **Robust Construction:** Includes double felt and a protective canvas for trays.

Optional Accessories

- Sublimation Paper 44"x30m and 64"x100m
- Lower Plate Polyester Felts
- Protective Nomex® Cover
- Non-stick Teflon Cover
- Silent Compressor: 50L-300L/min

Warranty

- **10 Years:** On heating elements.
- **2 Years:** On the machine.



Note: This is a non-contractual document. Characteristics may be modified depending on the evolution of the range.

